

Appl. No. 10/037,806

Amdt. dated October 6, 2004

Reply to Office action of August 9, 2004 **BEST AVAILABLE COPY**

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously presented) A method comprising:
performing, by a software stream, heap memory operations on a first end
of a linked list of free heap memory of a heap pile; and concurrently
returning a return block of heap memory, by a hardware device that used
the return block of heap memory, to the heap pile at a second end
of the linked list of free heap memory.
2. (Cancelled).
3. (Previously presented) The method as defined in claim 1 wherein
returning a return block of heap memory further comprises:
writing a null to a next block field of the return block of heap memory;
writing a block number of the return block of heap memory to a next block
field of a last block of heap memory in the linked list;
changing the contents of a bottom register to point to the return block of
heap memory; and thereby
making the return block of heap memory a last entry in the linked list.
4. (Previously presented) The method as defined in claim 1 wherein
performing heap memory operations further comprises returning, by the software
stream, a second block of heap memory by placing the second block of heap
memory at the first end of the linked list.
5. (Previously presented) The method as defined in claim 4 wherein
returning the second block of heap memory at the first end of the linked list by the
software stream further comprises:

Appl. No. 10/037,806
Amdt. dated October 6, 2004
Reply to Office action of August 9, 2004

determining a block number of a primary block of heap memory resident at the first end of the linked list;
writing the block number of the primary block of heap memory to a next block field of the second block; and
writing atomically a block number of the second block to a top register.

6. (Previously presented) The method as defined in claim 5 wherein determining a block number of a primary block of heap memory resident at the first end of the linked list further comprises reading the top register prior to writing the block number of the second block.

7. (Previously presented) The method as defined in claim 1 wherein performing heap memory operations further comprises removing, by the software stream, heap memory from the first end of the linked list.

8. (Previously presented) The method as defined in claim 7 wherein removing heap memory from the linked list heap management system further comprises taking a primary block of heap memory resident at the first end of the of the linked list.

9. (Previously presented) The method as defined in claim 8 wherein taking a primary block of heap memory further comprises:
determining a block number of the primary block;
reading a next block field of the primary block of memory; and
removing the primary block if the next block field of the primary block does not indicate a null.

10. (Original) The method as defined in claim 9 wherein determining a block number of the primary block further comprises reading a top register, wherein the top register identifies the beginning of the linked list.

Appl. No. 10/037,806
Amdt. dated October 6, 2004
Reply to Office action of August 9, 2004

11. (Original) The method as defined in claim 9 wherein removing the primary block if the next block field of the primary block does not indicate a null further comprises writing a block number of the next block field of the primary block to the top register.

12. (Previously presented) A method of managing a heap memory comprising:

maintaining unused blocks of heap memory as a linked list, and wherein the unused blocks of the linked list comprise a first block at a beginning of the linked list, a second block pointed to the first block, and a third block at an end of the linked list;

removing, by a software stream, the first block from the linked list, thus making the second block the beginning of the linked list; and

returning a return block, by a hardware device that used the return block, to the linked list by placing the return block at the end of the linked list.

13. (Previously presented) The method of managing a heap memory as defined in claim 12 wherein returning a return block further comprises:

writing a null to a next block field of the return block;

reading a bottom register, the bottom register identifying the third block;

writing a block number of the return block to a next state field of the third block; and

writing the block number of the return block to the bottom register.

14. (Original) The method of managing a heap memory as defined in claim 12 wherein removing, by a software stream, the first block from the linked list further comprises:

reading a top register, the top register identifying the first block;

reading a next block field of the first block, the next block field of the first block identifying the second block; and

Appl. No. 10/037,806
Amdt. dated October 6, 2004
Reply to Office action of August 9, 2004

writing a block number of the second block to the top register.

15. (Original) The method of managing a heap memory as defined in claim 14 wherein writing a block number of the second block to the top register further comprises atomically writing the block number of the second block to the top register.

16. (Original) The method of managing a heap memory as defined in claim 12 further comprising returning, by a software stream, a fourth block to the linked list by placing the fourth block at the beginning of the linked list, thus making the fourth block the beginning of the linked list.

17. (Original) The method of managing a heap of memory as defined in claim 16 wherein returning a fourth block to the linked list by placing the fourth block at the beginning of the linked list further comprises:

reading a top register, the top register identifying the beginning of the linked list;

writing a block number of the block identified by the top register to a next state field of the fourth block; and

writing a block number of the fourth block to the top register.

18. (Original) The method of managing a heap memory as defined in claim 17 wherein writing a block number of the fourth block to the top register further comprises atomically writing the block number of the fourth block to the top register.

19. (Previously presented) A method of managing a heap memory in a computer system, the method comprising:

allowing a software thread to add and remove blocks of heap memory from a linked list of free blocks of heap memory in a last-in/first-out (LIFO) fashion at a first end of the linked list; and

Appl. No. 10/037,806
Amdt. dated October 6, 2004
Reply to Office action of August 9, 2004

allowing a hardware device that uses blocks of heap memory to add the blocks of heap memory to the linked list of free blocks of heap memory at a second end of the linked list.

20. (Original) The method of managing a heap memory in a computer system as defined in claim 19 wherein allowing a software thread to remove blocks of heap memory in LIFO fashion further comprises:

determining, by the software thread, a block number of a block of heap memory at the first end of the linked list; and
removing the block of heap memory at the first end of the linked list.

21. (Original) The method of managing a heap memory in a computer system as defined in claim 20 determining a block number of a block of heap memory at the first end of the linked list further comprises reading a beginning register that stores a block number of a block of heap memory at the first end of the linked list.

22. (Original) The method of managing a heap memory in a computer system as defined in claim 21 wherein removing the block of heap memory at the first end of the linked list further comprises:

reading a next block field of the block of heap memory at the first end of the linked list to identify a block number of a next block in the linked list; and
writing the block number of the next block in the linked list to the beginning register.

23. (Original) The method of managing a heap memory in a computer system as defined in claim 20 wherein allowing a software thread to add blocks of heap memory in LIFO fashion further comprises:

determining, by the software thread, a block number of a block of heap memory at the first end of the linked list;

Appl. No. 10/037,806
Amdt. dated October 6, 2004
Reply to Office action of August 9, 2004

writing the block number of the block of heap memory at the first end of the linked list to a next block field of a return block of heap memory;
and
making the return block of heap memory the first end of the linked list.

24. (Original) The method of managing a heap memory in a computer system as defined in claim 23 wherein determining a block number of a block of heap memory at first end of the linked list further comprises reading a beginning register that stores a block number of a block of heap memory at the first end of the linked list.

25. (Original) The method of managing a heap memory in a computer system as defined in claim 24 wherein making the return block of heap memory the first end of the linked list further comprises writing a block number the return block of heap memory to the beginning register.

26. (Previously presented) The method of managing a heap memory in a computer system as defined in claim 20 wherein allowing a hardware device that uses blocks of heap memory to add the blocks of heap memory to the linked list of free blocks of heap memory at a second end of the linked list further comprises:

determining, by the hardware device, a block number of a block of heap memory at the second end of the linked list;
writing, by the hardware device, a block number of a return block of heap memory to a next block field of the block of heap memory at the second end of the linked list; and
making the return block of heap memory the second end of the linked list.

27. (Original) The method of managing a heap memory in a computer system as defined in claim 26 wherein determining a block number of a block of heap memory at the second end of the linked list further comprises reading an end

Appl. No. 10/037,806
Amdt. dated October 6, 2004
Reply to Office action of August 9, 2004

register that stores a block number of the block of heap memory at the second end of the linked list.

28. (Original) The method of managing a heap memory in a computer system as defined in claim 27 wherein making the return block of heap memory the second end of the linked list further comprises writing a block number the return block of heap memory to the end register.

29. (Previously presented) A computer system comprising:
a microprocessor executing a software stream;
a main memory array, a portion of the main memory array allocated to be a heap memory, and wherein unused portions of the heap memory are part of a heap pile, the heap pile further comprising
a plurality of blocks;
each block having a next block field; and
wherein the heap pile is maintained as a linked list, each block's next block field pointing to a next block in the list;
a first bridge logic device coupling the microprocessor to the main memory array;
a hardware device coupled to the heap memory through the first bridge logic device;
wherein the software stream executed on the microprocessor removes blocks of heap memory from a beginning of the heap pile; and
simultaneously
the hardware device returns blocks of heap memory used by the hardware device to an end of the heap pile.

30. (Previously presented) The computer system as defined in claim 29 wherein the plurality of blocks each have the same number of bytes.

Appl. No. 10/037,806
Amdt. dated October 8, 2004
Reply to Office action of August 9, 2004

31. (Cancelled).

32. (Previously presented) The computer system as defined in claim 29 further comprising the software stream returns blocks to the heap pile at the beginning of the heap pile simultaneously as the hardware device returns blocks of heap memory used by the hardware device to the end of the heap pile.

33. (Original) The computer system as defined in claim 29 wherein the hardware device is the graphics card.

34. (Original) The computer system as defined in claim 29 wherein the hardware device is a network interface card.

35. (Original) The computer system as defined in claim 29 wherein the hardware device is an audio card.

36. (Original) The computer system as defined in claim 29 wherein the hardware device is a mass storage device.

37. (Original) The computer system as defined in claim 36 wherein the mass storage device is a hard drive.

38. (Original) The computer system as defined in claim 37 wherein the mass storage device is compact disk storage device.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.